

Technical Data Sheet

Premium Whiteboard Ink – WB1500 Series

WB1500 series is our latest colourful generation of pigmented dry erase ink. This vibrant range can be erased quickly and cleanly from a whiteboard, due to the quick drying time. Enhanced marker storage stability* and up to 72 hours cap-off time* can also be achieved with these inks. Regulatory information and compliance available on request.

*component dependent

● Standard Colours (other shades available on request)

Ink Colour	Pantone References*	Typical Viscosity (20°C) (mPa.s)	Density (20°C) (g.cm ⁻³)	Surface Tension (mNm/m)
● WB1573 Black	N/A	9.0	0.83	27
● WB1574 Blue	2145 C	5.5	0.83	27
● WB1566 Cyan	3538 C	5.5	0.83	27
● WB1587 Red	032 C	8.5	0.83	27
● WB1570 Green	3500 C	5.0	0.83	27
● WB1535 Green	2240 C	7.5	0.83	27
● WB1578 Lemon Grass	2421 C	6.0	0.83	27
● WB1569 Yellow	101 C	5.5	0.83	27
● WB1568 Orange	151 C	8.0	0.83	27
● WB1575 Pink	674 C	10.5	0.83	27
● WB1576 Purple	267 C	5.5	0.83	27
● WB1586 Brown	7594 C	9.0	0.83	27

*Pantone references quoted are approximate to give an indication of colour shade

● Component Selection Advice

For optimum performance, markers should ideally be stored in the horizontal orientation and should be capped securely.

Nib - Polyester or acrylic (high porosity) around 65%

Reservoir - Polyester with polypropylene wrapping and a density of 0.18 g.cm⁻³

Barrel - Polypropylene (PP), polyethylene (PE), aluminium

Head/tail caps - Polypropylene (PP), polyethylene (PE), BS 7272-1:2008 compliant

Please test and approve our inks in your own components

● Shelf Life

The shelf life of WB1500 series inks is 24 months from receipt when stored in the original sealed containers. It is recommended to store the inks between 10°C and 30°C.

Drums should be stored for at least 24 hours at room temperature (around 20°C) and then thoroughly agitated until the ink is uniform before to use.

Caution: Whiteboard inks are flammable liquids, so please handle accordingly. For more information, please refer to the Material Safety Data Sheet.

✉ For further information please email lab@multichem.net

Disclaimer: It is your responsibility as the writing instrument manufacturer to establish the overall safety and fitness for purpose of the marker components incorporating our inks and to establish overall compliance to regulations and legislation related to the industry. All marker pen components should be thoroughly tested by you for compatibility with our inks. Multichem makes no guarantees (either express or implied) with respect to this technical data or our advice regarding component selection. Multichem will not accept any liability for any loss arising in connection with this technical data or the recommendations expressed within (other than that resulting from our gross negligence). Please contact your component suppliers for more specific advice regarding component suitability and selection. The information contained within this technical data sheet is not exhaustive and you should verify the performance of your final product.